

What is claimed is:

1. An electroluminescence light emitting display system comprising:

an electroluminescence light emitting sheet which comprises a light-emitting layer containing electroluminescence light-emitting elements therein, and an electrode section comprising a plurality of electrode pairs which are disposed with a predetermined arrangement, wherein each of the electrode pairs includes first and second electrodes which are electrically separated from each other with a spacing region and disposed in one surface side of the light-emitting layer with a predetermined arrangement; and

a voltage application unit for applying a predetermined voltage between the first and second electrodes,

wherein when an electrically conductive material is placed on the other surface side of the light-emitting layer and a voltage application between the first and second electrodes is performed by the voltage application unit, a portion of the light-emitting layer corresponding to the placed electrically conductive material emits light; and each width of the first and second electrodes is 0.2-0.5 mm and a width of the spacing region between the first and second electrodes is 0.2-0.3 mm.

2. The electroluminescence light emitting display system as claimed in claim 1, wherein the electrically conductive material is attachable onto and detachable from the other surface side of the light-emitting layer.

3. The electroluminescence light emitting display system as claimed in claim 1, wherein the electrode section comprises a plurality of electrode pairs.

4. The electroluminescence light emitting display system as claimed in claim 2, wherein the electrode section comprises a plurality of electrode pairs.

5. An electroluminescence light emitting sheet comprising:

a light-emitting layer containing electroluminescence light-emitting elements therein; and an electrode section comprising a plurality of electrode pairs which are disposed with a predetermined arrangement, wherein each of the electrode pairs includes first and second electrodes which are electrically separated from each other with a spacing region and disposed in one surface side of the light-emitting layer

with a predetermined arrangement, each width of the first and second electrodes is 0.2-0.5 mm and a width of the spacing region between the first and second electrodes is 0.2-0.3 mm.

6. The electroluminescence light emitting sheet as claimed in claim 5, wherein the electrode section comprises a plurality of electrode pairs.